

## Master-Grip Quick-Fix Clamp

**Special clamp for right-lay hoses**



### Material

- band collar, bridge, socket: stainless steel (1.4301)

### Applications

- Special clamp for lighter and medium duty, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR, Master-PVC and Master-SANTO

### Properties

- robust
- rust-free
- primarily tight and tear-proof connection via bridge profiles
- adjustable clamping force via clamping screw
- very easy to install
- subsequent quick mounting also possible for pre-installed hoses

### Product Variations

for right-hand hoses in DN	clamping range in mm	article-no.
75	75-82	534-075-888
80	80-87	534-080-888
90	90-97	534-090-888

100	100-107	534-100-888
110	110-117	534-110-888
120	120-127	534-120-888
125	125-132	534-125-888
130	130-137	534-130-888
140	140-147	534-140-888
150	150-157	534-150-888
160	160-167	534-160-888
170	170-177	534-170-888
175	175-182	534-175-888
180	180-187	534-180-888
200	200-207	534-200-888
215	215-222	534-215-888
225	225-232	534-225-888
250	250-257	534-250-888
275	275-282	534-275-888
300	300-307	534-300-888
315	315-322	534-315-888
325	325-332	534-325-888
350	350-357	534-350-888
375	375-382	534-375-888
400	400-407	534-400-888
450	450-457	534-450-888
500	500-507	534-500-888

All data refers to a medium and ambient temperature of +20 °C.

\* Refers to the inner hose lining

Subject to technical changes and colour deviations.

#### Available from stock

- Clamping range from 75/82 mm to 500/507 mm

#### Available on request

- Available on request in other sizes and materials.