

LEVEL GAUGE MODEL		PROCESS				STEAM		
		VALVE/COCK	RATING - P MAX	P MAX (bar)	T MAX (°C)	VALVE/COCK	P MAX (bar)	T MAX (°C)
REFLEX	K	-	-	-	-	D	32	239
	R 25	DG-RAV	PN 25 / ANSI 150	25	400	D	20	215
	R 100	DG-RAV	PN 100 / ANSI 600	100	400	D	22	219
	R 160	DG-RAV	PN 160 / ANSI 900	160	400	D	32	239
	R 250	RAV	PN 250 / ANSI 1500	250	400	-	-	-
	UOR Large Chamber	DG-RAV	PN 63 / ANSI 400	63	400	-	-	-
	A 400	DVK2.IT	PN 400 / ANSI 2500	400	120	-	-	-
TRANSPARENT	R-D glass tube	D	PN 16	16	185	D	10	185
	T 50	DG-RAV	PN 50 / ANSI 300	50	400	D	15	202
	T 100	DG-RAV	PN 100 / ANSI 600	100	400	D	30	235
	T 160	DG-RAV	PN 160 / ANSI 900	160	400	D – DA	40	252
	T 160–XS	DG-RAV	PN 160 / ANSI 900	160	400	D – DA	50	265
	T 250	RAV	PN 250 / ANSI 1500	250	400	-	-	-
	UOT Large Chamber	DG-RAV	PN 63 / ANSI 400	63	400	-	-	-
	T 85	-	-	-	-	DA – RAV 957 - DVK2.IT	85	298
	TA 120	-	-	-	-	DA	85	298
TA 120	-	-	-	-	DVK2.IT	120	323	
WELD PAD	UWR / UWT	-	PN 100 / ANSI 600	100	400	-	-	-
	USR / UST	-	PN 100 / ANSI 600	100	400	-	-	-
BICOLOUR	KTA	-	-	-	-	DVK2	180	356